Fully Compensated Dual Counterbalance Valve - Flanged

Valvola Overcenter Doppia Compensata - Flangiata

WODFC 60 – 1F

TECHNICAL DATA

- **Flow:** 60 l/min
- **Max setting pressure:** 350 bar
- **Materials:** Steel Body
- **Pilot ratio:** 4:1 (if request 1:1; 8:1; 11:1)
- **Weight:** See Table

- **Note:** - Pressure setting must be 30 % higher that pressure induced by the load.
  - Recommended for use with closed center spools.



PORTS		
C1 V1 - V2	3/8	1/2
C2	ø9	
M	1/4	
DIMENSIONS		
A	55	65
B	29,5	34,5
C	14,5	17
D	19	18
E	112	114
Weight (kg)	1,700	2,100



PRESSURE DROP CURVES



SPRINGS						
Code	20			35		
Pilot ratio	Adjustable pressure range bar	Pressure increase bar/turn	Standard setting bar	Adjustable pressure range bar	Pressure increase bar/turn	Standard setting bar
1:1	10-70	15	10	30-200	25	30
4:1	60-210	70	170	80-350	120	280
8:1	60-220	50		100-350	85	
11:1	60-250	90		80-350	150	

ORDERING CODE

WODFC | 60 | [ ] | 1F | [ ] | [ ] | [ ]

Ports Size:
- 3/8
- 1/2

Springs:
- 20
- 35

Pilot Ratio:
- Omit if 4:1
- 1 = 1:1
- 8 = 8:1
- 11 = 11:1

Adjustment if Required:
- Omit if not required
- Value